

Two Stage — Gasoline



AM2-PK95-08M

Used to power a multitude of air tools, the two stage wheelbarrow style 8-gallon air compressor is ideal for contractors, remodelers and anyone who needs air power. It offers a high CFM and air pressure and is designed for hard work and longevity.

Compressor Pump:

Splash lubricated | Stainless-steel braided discharge hose | Large canister intake filter | Oil level sight indicator

Frame:

Powder coated 8-gallon twin tank receivers | 3/16-inch base plate to reduce vibration | 14-gauge powder coated two-piece belt guard | 10-inch flat-free tires

Components:

Regulator and two gauges for tank and outlet pressure | Manual drain valves for proper maintenance | 16½-inch fly wheel | Quality pilot valve unloader

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler CH395 OHV	Two stage, cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.

***Equipped with 150-PSI maximum rated regulator.**



8-Gallon

Air Compressors – Two Stage – Gasoline

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl - Drains moisture from air system	All models
AX-0015	Electric start - battery and cables not included - For easy starting	AM2-PH09-08M
IX-0055	Remote start/choke - 6-ft. wire extension for key switch. You will also need to order electric start option, AX-0015.	AM2-PH09-08M
IX-0059	Remote start/choke - 6-ft. wire extension for key switch, sealed cable. You will also need to order electric start option, AX-0015.	AM2-PH09-08M

Accessory:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models



AM2-PH09-08M

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.